Recuplastik IV Seed Maize

The GAINE IV recovery is the latest evolution of this type of equipment. It takes into account the demands of users to **collect more**, **faster** with less waste.

Composed of a lifting mast and a rotating head driven by a cylinder giving it a *working angle of 111*°. The collection is done from the side or from the front. The head of the machine is located at 2.80 m from the ground when it is unfolded, allowing the bales to be emptied into 20 m³ skips or agricultural skips

Its innovative design with :

- Its rotating head
- Its centre of gravity close to the tractor
- Its opening kinematics
- Its guiding and cleaning ring

make it the **most powerful machine** on the market.

Ergonomics and safety have not been forgotten:

- The markings of all the connectors with the diagram engraved on the chassis
- The easy-to-use valve block

Designed for the collection of drip tubes and also 500 hole, mulch, forcing and greenhouse films as well as its nets and P17 propylene sails.

Machine performance table	
Tractor power required	90 to 130 hp
Hydraulics	Tractor return valve direct tank
Power supply	12 VDC
Weight	800 Kg
Length	2,50 meters
Width	1,90 meters
Height	2,40 meters
3-point linkage front and rear	Category 2
Ballast	See notice
Forward speed	0 to 25 Km/h
umber of sheaths harvested and cleaned	From 1 to 10
Coil diameter	800 mm
GROUNDED SHEATHS	