

RECUP V

The RECUP V model with lifting mast and head rotation by hydraulic cylinder on 135° allows to reproduce the manual collection.

The speed of the reel is regulated from a control box in the tractor cab. The hydraulically rotating head allows the film to be picked up from the front and from the right or left side. The concept of picking up the film from the side, far away and in elevation allows to evacuate the soil and to remove the plastic film from the plants, by shaking without adding a brush.

The bale is released by hydraulically opening the cones vertically and can be placed directly into a skip.

Compliance and safety elements.

The machine has few components. The film path can be followed from the tractor cab without any discomfort.

The operator can stop the rotation of the hydraulic motor at any time from his transport position on the machine's footboard. This function is fulfilled by an emergency stop button.

Versatile use of collection: tunnel, mulch, irrigation sheath, 500 holes non-woven...

Attachment to the front or rear of the tractor

Electrical control from the driver's cab (12VDC powered control box)



OPTION

Digging tooth

Performance table

Ref.	Packing			Weigh t	Performance
	Length	Width	Height		
RECUP V 2,00	2,50	2,40	590Kg	1 driver 1 operator Forward speed = 4 to 10 Km/h Roll capacity = 2500m of plastic film (60micron, width 2m) Tractor power = 85hp to 120hp 4WD	