

## **Decompactor 3 teeth**

Parallel double V frame made of high quality steel tube with a large cross-section allowing a good distribution of the forces on each of the beams. Third point triangle and non-deformable tubular counter plug. The blade supports are made of high resistance steel. These have a judiciously studied shape to allow the most agronomic work possible, less clods, low power consumption as well as a very good penetration in the soil. No surface disturbance, no rotation or inertia of the clods, just cracking and lifting of the soil.

The blades are protected by a triangular hardened steel seam.

Each blade is secured by a shear bolt that breaks at 28 tons, allowing work to be carried out in the most difficult conditions.

The forged and hardened steel ploughshares are fitted with hollow head bolts (BTR) and nuts for easy disassembly. They are provided with several holes allowing them to be advanced as they wear.

### **It can be equipped with several types of rollers:**

Combined bar and disc roller

Serrated disc roller

Culti-packer roll

They are mounted on Timken® dual bearings that react to vertical and lateral forces, allowing you to work on slopes in optimal conditions.

In addition, the roller allows the load to be transferred to the front axle and avoids any buckling, thus ensuring perfect transmission of power to all four wheels.

The depth adjustment can be done by screw jack or hydraulic cylinder.

### **Technical specifications**

Available with 1, 3, 5, 7 and 9 teeth. Interchangeable coulter.

Working depth = 60cm.

Clearance under frame = 0,80cm



## **Performance table**

| Ref.       | Packing |       |        | Weig<br>ht  | Performance |
|------------|---------|-------|--------|---|-------------|
|            | Length  | Width | Height |   |             |
| DP3DR 1.40 | 2,45    | 1,60  | 700Kg  | 1 driver<br>Speed = 4 to 8Km/h<br>Tractor power = 90 to 110hp 4WD |             |